

TOYOTA 79 SERIES

4200KG GVM UPGRADE

Kit #: TOYKIT080-GVM



Capacities	Lovells	OE
GVM	4200kg	3300kg
GCM	7400kg	6800kg
Front Axle	1650kg	1460kg
Rear Axle	2550kg	2300kg
Towing	3500kg	3500kg

DATES

Single Cab
01/2017-08/2022

Dual Cab
01/2018-08/2022

SPRING OPTIONS

FRONT: TFS-79 – Minimal load bearing front accessories, including Bullbar. 0 – 100kg Constant Load
TFR-79 – Minimal load bearing front accessories, including Bullbar, winch. 100 – 150kg Constant Load

REAR: TL-79XHD – Heavy Duty Leaf Spring (11 Leaf), 400 to 500kg Constant Load
TL-79SR – Heavy Duty Leaf Spring (12 Leaf), 500 to 600kg Constant Load

SHOCK PART NUMBERS

FRONT: 64612491 (Twin Tube Shocks)
REAR: 64612492 (Twin Tube Shocks)

NOTES:

SVI Plate Location:
RHS Firewall

Lovells Approval Number:
VTA 025742

Tyres:

**TYRES MUST BE CHANGED TO
A MINIMUM LOAD RATING
OF 117 & SPEED RATING OF M**

Special Requirements:

**CAT6 indicators are required to
be compliant**

Always consult Lovells master data capacities
spreadsheet, these data sheets are a guide only

OTHER KIT COMPONENTS

Eye & Shackle Bushed
Caster Correction Bushes (Additional fitting time required)
U-Bolts
Greaseable Shackles
Greaseable Pins
Rear Handbrake Cable Extension Bracket
Tyre Placard
Decals

TYRE – LOADING INFORMATION

	FRONT AXLE			REAR AXLE		
TYRE SIZE <small>(minimum)</small> <small>(Tyre Load Index minimum)</small>	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)
RIM SIZE <small>(minimum)</small>	16X6J	16X5.50F	16X7J	16X6J	16X5.50F	16X7J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (240kPa)	250kPa (240kPa)	300kPa (250kPa)	475kPa (260kPa)	475kPa (260kPa)	450kPa (250kPa)
LOAD CARRYING CAPACITY PER AXLE <small>(maximum)</small>	1650kg			2550kg		
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE						
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.						
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "M" (130km/h).						
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG						
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 4200kg						

LS-LC79ANCAPTP V3 4200

*GCM revision may not be
available in all states.

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au



9th May 2025