

TOYOTA PRADO 250 SERIES

3650KG GVM UPGRADE

Kit #: TOYKIT088-GVM-LT36

Capacities	Lovells	OE
GVM	3650kg	3100kg-3200kg
GCM	6800kg *	6600kg
Front Axle	1605kg	1605kg
Rear Axle	2045kg	1860kg
Towing	3500kg	3500kg

DATES

2024 on

SPRING OPTIONS

FRONT: TFR-250 – Standard Coil, 0kg – 80kg Constant Load
TFS-250 – Optional Coil, 0kg – 80kg Constant Load
TFR-250HD – Optional Coil if Bullbar and Winch fitted

REAR: TRR-251 – Standard Coil, 0kg – 100kg Constant Load
TRS-251 – Optional Coil, 0kg – 100kg Constant Load
TRR-251HD – Optional Coil , 0kg – 100kg Constant Load

SHOCK PART NUMBERS

FRONT: 64611062 (Twin Tube Shocks)
REAR: 64611063 (Twin Tube Shocks)

OTHER KIT COMPONENTS

CAT 6 Indicators & Harness
Decals
Tyre Placard

NOTES:

SVI Plate Location:

Passengers Side B Pillar

Lovells Approval Number:

VTA 065547

Tyres:

Factory tyres meet minimum specification

Special Requirements:

CAT6 Indicators must be fitted

Always consult Lovells master data capacities spreadsheet, these data sheets are a guide only



TYRE LOADING INFORMATION

RECOMMENDED COLD TYRE INFLATION PRESSURE kPa (LOADED)

	FRONT AXLE	REAR AXLE
LOAD CAPACITY PER AXLE	1605kg	2045kg
265/65R18 114V 18X7.5J	230 (250)	230 (250)
265/70R18 116H 18X7.5J	230 (250)	230 (250)
265/60R20 112H 20X7.5J	230 (250)	230 (250)

CONSTANT PAYLOAD OF 250KG RECOMMENDED
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3650kg

PRADO 250 A1 3650

*GCM revision may not be available in all states.

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au



1st December 2025