

FORD RANGER NEXT GEN 3700KG GVM UPGRADE



Kit #: FORDKIT019-GVM-LT

| Capacities | Lovells | OE |
|------------|----------|--------|
| GVM | 3700kg | 3280kg |
| GCM | 7200kg * | 6400kg |
| Front Axle | 1640kg | 1490kg |
| Rear Axle | 2120kg | 1959kg |
| Towing | 3500kg | 3500kg |

| DATES |
|---|
| All body types 3.0 Ltr V6 Engine 2022 on |

| <u>SPRING OPTIONS</u> | |
|------------------------------|--|
| FRONT: | FFS-92 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1400kg FFR-92 – Load bearing front accessories, including Bullbar, winch. Axle capacities over 1400kg |
| REAR: | FR-2XHD – Only Rear Leaf Spring Available, 400kg – 500kg Constant Load |

| <u>SHOCK PART NUMBERS</u> | |
|----------------------------------|-----------------------------|
| FRONT: | 64612857 (Twin Tube Shocks) |
| REAR: | 64612858 (Twin Tube Shocks) |

| <u>OTHER KIT COMPONENTS</u> | |
|------------------------------------|-------------------|
| Eye & Shackle Bushes | Wedge |
| U-Bolts | Tail Shaft Spacer |
| Greasable Shackles | |
| Greasable Pins | |
| Tail Shaft Spacer | |
| Spring Wedges | |
| Tyre Placard | |
| Decals | |

| <u>NOTES:</u> |
|---|
| SVI Plate Location: Passengers Side B Pillar |
| Lovells Approval Number: VTA 061527 |
| Tyres: Factory tyres meet minimum specification |
| Special Requirements: |

| TYRE – LOADING INFORMATION | | | | | |
|--|----------|---|-----------|--------------------------------------|-----------|
| TYRE SIZE | RIM SIZE | RECOMMENDED COLD INFLATION PRESSURE (kPa) | | INFLATION PRESSURE AT MAX LOAD (kPa) | |
| | | FRONT AXLE | REAR AXLE | FRONT AXLE | REAR AXLE |
| 255/70R16 (111T) | 16x7J | 230 | 250 | 260 | 300 |
| LT255/70R16 (114S) | 16x7J | 230 | 250 | 260 | 320 |
| 255/70R17 (112T) | 17x7.5J | 230 | 250 | 260 | 300 |
| LT265/70R17 (114S) | 17x8J | 230 | 250 | 260 | 325 |
| 255/65R18 (111H) | 18x7.5J | 230 | 250 | 260 | 300 |
| LT265/65R18 (114R) | 18x7.5J | 230 | 250 | 260 | 330 |
| 255/55R20 (110V) | 20x8J | 240 | 250 | 260 | 300 |
| LOAD CARRYING CAPACITY PER AXLE (maximum) | | FRONT AXLE 1640kg | | REAR AXLE 2120kg | |
| SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 300KG | | | | | |
| THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3700kg | | | | | |

LS Ranger 3 3700 V3

*GCM revision may not be available in all states.

20th February 2025

Ph: +61 2 9820 6800

Email sales@lovells.com.au
www.lovellsauto.com.au

