TOYOTA 200 SERIES

3800KG GVM UPGRADE

Kit #: TOYKIT067-GVM-D

| Capacities | Lovells | OE |
|------------|----------------------|--------|
| GVM | 3800kg | 3350kg |
| GCM | 7300kg (Diesel Only) | 6800kg |
| Front Axle | 1800kg | 1630kg |
| Rear Axle | 2000kg | 1950kg |
| Towing | 3500kg | 3500kg |



All models Petrol & Diesel 11/2007 - 2022

SPRING OPTIONS

FRONT: TFR-121 — Minimal or no load bearing front accessories.

TFR-123 — Light Load bearing front accessories, Alloy Bullbar, Light Steel Bullbar

TFR-123HD — Heavy Load bearing front accessories, Steel Bullbar, Winch.

REAR: TRR-122HD — Minimal load bearing rear accessories. Axle capacities under 1600kg

TRR-122HDAV — Heavy load bearing rear accessories. Axle capacities over 1600kg

SHOCK PART NUMBERS

FRONT: 64611007 (Twin Tube Shocks)

REAR: 64611008 (Twin Tube Shocks)

OTHER KIT COMPONENTS

Decals

Tyre Placard

NOTES:

SVI Plate Location:

Drivers Side Lower B Pillar

Lovells Approval Number:

VTA 040257

VTA 046734 (BTC)

Tyres:

Factory tyres meet minimum

specification

Special Requirements:

| | FRONT AXLE | | REAR AXLE | |
|---|---------------------|---------------------|---------------------|---------------------|
| TYRE SIZE (minimum) (Tyre Load Index minimum) | 285/65 R17 (116) | 285/60 R18 (116) | 285/65 R17 (116) | 285/60 R18 (116) |
| RIM SIZE (minimum) | 17X8J | 18X8J | 17X8J | 18X8J |
| RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load) | 230kPa (230kPa) | 230kPa (230kPa) | 230kPa (230kPa) | 230kPa (230kPa) |
| LOAD CARRYING CAPACITY PER AXLE (maximum) | 1800kg | | 2000kg | |

(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.

THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q" (160km/h).

SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 250KG

THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED $3800 \mathrm{kg}$

LS-LC200 V4 3800

