

VEHICLE DATA SHEET

TOYOTA LC79 SERIES J7 (Sept 2022-on) 4200KG GVM UPGRADE



APPLICABLE VARIANTS: Double Cab-Workmate & GXL, Single Cab-WM, GX, GXL
FUL GDJL79R-TJTRYQ3, FUL-GDJL79R-TJTNYQ3, FUL-GDJL79R-DKTRYQ3, FUL-GDJL79R-DKTNYQ3,
FUL-VDJL79R-TJMRYQ3, FUL-VDJL79R-TJMNYQ3, FUL-VDJL79R-DKMRYQ3, FUL-VDJL79R-DKMNYQ3,
NB1 - Medium Goods Vehicle

GVM UPGRADE LIMIT: 4200 kg (OE Spec. 3510kg)

FRONT AXLE LIMIT: 1630 kg (OE Spec. 1460kg)

REAR AXLE LIMIT: 2570 kg (OE Spec. 2300kg)

RVSA APPROVAL #: VTA-064032 (OE Spec. VTA-060702)

FULCRUM SUSPENSION PTY LTD KIT PART #: CRUS-79J7GVM

LC 78 or 79 Part #'s CRUS-78J7GVM, CRUS-79J7GVM

VEHICLE	Toyota Landcruiser - LC70	KIT PART #	CRUS-78J7GVM, CRUS-79J7GVM
Part #	Description	Quantity per	UoM
KTFR-74HD	Front Spring	1	PR
60006	Front Shock/Damper	2	EA
FLS-032P	Rear Spring 700kg cons.	2	EA
60007	Rear Shock/Damper	2	EA
KIT193SK	Bushes, shackles & pins	1	KT
SPF1721K	Radius Arm Castor Bush	1	KT
FUB-002	U Bolt	4	EA
LC70LOADCL	Load Capacity Label (78&79 Series)	1	EA
LC70PLACARD	Tyre Loading Placard (Decal)	1	EA
GVMLC70DK	Fitting Instructions, Installation Checklist, Owner's Manual, Kit List & Fulcrum Suspensions Safety Inspection Report	1	EA

TYRE PRESSURE & LOADING INFO



GVM UPGRADE CAPACITY-LC78&79	4200kg
FRONT AXLE CAPACITY	1630kg
REAR AXLE CAPACITY	2570kg

	TYRE SIZE	L/S RATING	FRT	RR	
UNLADEN	225/95R16C	118S	240 35	260 38	kPa psi
	265/70R16LT	*117S	250 36	250 36	kPa psi
LADEN	225/95R16C	118S	260 38	475 69	kPa psi
	265/70R16LT	*117S	290 42	450 65	kPa psi

Tyre load ratings shall always be greater than half the capacity of the axle they are mounted on.

*Note: Tyre change required for 265/70R16LT from 115 to 117 and Speed Rating of S



LC70PLACARD

NOTES

- SVI Plate Location: RHS Firewall or nearest practical position
- Tyres: OE tyres accepted

